



V SERIES

**DIGITAL
CAPACITANCE
METER**

Model : V 6013

3 ½ Digits

WITH BACK-LIGHT

**9 RANGES from
200 pF to 20000 µF**

WITH HOLSTER



PLEASE 'DISCHARGE' CAPACITORS BEFORE TESTING

| SPECIFICATIONS | | |
|-------------------------------|--|--------------------------|
| RANGE | MEASURING FREQUENCY | ACCURACY |
| 200 pF | 800 Hz | ± (0.5 % rdg + 7 digits) |
| 2 nF | | ± (0.5 % rdg + 5 digit) |
| 20 nF | | |
| 200 nF | | |
| 2 µF | 80 Hz | ± (2 % rdg + 5 digits) |
| 20 µF | | |
| 200 µF | 8 Hz | ± (3 % rdg + 10 digits) |
| 2,000 µF | | |
| 20,000 µF | | |
| Protection | Provided, with Fuse. | |
| Power source | 9 V (6F22) | |
| Accessories Supplied | Test Leads, User Manual & Battery (Installed / Kept Aside) | |
| Dimension & Weight | 189 x 97 x 35 mm & Approx. 320 gms. (Incl. Batt.) | |

** All Specifications & appearances are subject to change without prior notice.*