



**V**SERIES

# DIGITAL MULTIMETER

**Model : V 92 A**

**3 1/2 Digits**

**Auto / Manual Ranging**

**Auto Power Off**

**Data Hold & Max. Value Hold**

**Temp., Measurement (°F & °C)**

**200 mV Range in ACV Also**

**DC & AC 200 µA Range**

**LARGE Fine L.C.D.**

**WITH HOLSTER**



SPECIFICATIONS		
DC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 600 V
	Basic Accuracy	± (0.5 % rdg + 4 digits)
AC voltage	Range	200 mV, 2 V, 20 V, 200 V, 600 V
	Basic Accuracy	± (0.8 % rdg + 6 digits)
DC current	Range	200 µA, 2000 µA, 20 mA, 200 mA, 10 A
	Basic Accuracy	± (1 % rdg + 10 digits)
AC current	Range	200 µA, 2000 µA, 20 mA, 200 mA, 10 A
	Basic Accuracy	± (1.5 % rdg + 10 digits)
Resistance	Range	200 Ω, 2 KΩ, 20 KΩ, 200 KΩ, 2 MΩ, 20 MΩ
	Basic Accuracy	± (0.8 % rdg + 4 digits)
Temperature	Range	- 20 °C ~ 1000 °C (0 °F ~ 1832 °F). °C & °F Selectable.
Input impedance in DCV & ACV		200 mV Range : > 40 M Ω & Other Ranges : 10 M Ω
Frequency Response in 'AC'		50 ~ 200 Hz
Continuity Test & Diode Test		Provided
Other Facilities / Features		Data Hold, Max. Value Hold, Auto Power Off, Low Batt., Indication, 2 x 'AAA' Battery Operation.
Accessories Supplied		Holster, Test Leads, User Manual, Battery (Installed / Kept Aside) & Temperature Probe.
Dimension & Weight		145 x 74 x 36 mm & Approx. 185 gms. (With Batt.)

*\* All Specifications & appearances are subject to change without prior notice.*