



DIGITAL CLAMP

MULTIMETER

3 ³/₄ Digits

AUTO RANGING

Model :-

MS 2008 B

AUTO POWER-OFF
DOUBLE INJECTION MOULDED BODY
BACK LIGHT
CLAMP LIGHTING
FREQUENCY & CAPACITANCE
MEASUREMENTS



FEATURES

- *DOUBLE INJECTION MOULDED BODY*
- *AUTO RANGING & AUTO POWER OFF*
- *Conform to the IEC1010-1 standard CAT III 600V*

SPECIFICATIONS :-

- DC voltage: 400mV/4V/40V/600V $\pm 0.8\%$
- AC voltage: 400mV $\pm 3.0\%$, 4V/40V/600V $\pm 1.0\%$
- AC current: 4A/40A/400A/600A $\pm 2.0\%$
- Resistance: 400 Ω /4k Ω /40k Ω /4M Ω $\pm 1.2\%$, 40M Ω $\pm 2.0\%$
- Capacitance: 50n/500n/5 μ /50 μ /100Mf $\pm 4.0\%$
- Frequency: 50/500/5000/50k/100kHz $\pm 1.0\%$
- Temperature: -20°C ~ 750°C
- MAX. diameter for conductor: $\Phi 26\text{mm}$
- Back light
- Clamp lighting
- Diode test
- Continuity test
- Duty cycle test
- Power: AAA (1.5V) x 3
- Size: 208mm x 78mm x 35mm
- Weight: Approx. 240g (w/o battery)